



HAWK-301CD

1/3" Color Indoor Dome Camera. Sony SuperHad Chip, mid-resolution, 420 Lines. Only 3 3/8" in diameter. 3.6mm Lens 12V DC. Backlight Compensation, Electronic Iris.

KEY FEATURES

1/3" SONY SUPER HAD 420TVL

Mid Resolution Image Sensor Built-in.

Min Illumination : 0.2 Lux

Gimbal mount for free turning of the Lens

12V DC

www.hawkisecurity.com

Hawk-I Security 355 Oser Ave, Hauppauge, N.Y. 11788 Ph: 631-656-1056 Fax: 631-656-1054

HAWK-301CD

SPECIFICATIONS

Image Sensor	1/3" SONY SUPER HAD 420TVL:
Min. Illumination	0.3 Lux/F2.0
Scanning Frequency Horizontal:	15,734Hz NTSC
Video output Level	1.0Vp-p (75ohms, Composite)
S/N Ratio	More than 48dB (AGC Off)
Gamma	r = 0.45
White Balance	2,100°K - 9200°K - Auto
Gain Control	4dB - 32dB - Auto
IRIS Control	Auto
Backlight Compensation	On
Operating Temp/Humidity	14°F - 122°F (10% - 95% RH)
Lens	3.6mm
MTBF	80,000 Hours,
Power Source	DC12V 60mA
Dimensions	(HxD) 3" x 3 3/8"
Net Weight	0.5 ounces

www.hawkisecurity.com

Hawk-I Security 355 Oser Ave, Hauppauge, N.Y. 11788 Ph: 631-656-1056 Fax: 631-656-1054