



HAWK-360VIRCD

Vandalproof and Weatherproof, this Varifocal Color Dome Camera has external controls for distance and focus. It works in no light up to 60 feet away with IR Led's. Accidental surge and shock protection.

Key Features

- 1/3" SONY SUPER HAD 420 TVL High Resolution Image Sensor Built-in
- Outstanding high Sensitivity picture quality under extreme low illumination
- All direction adjustable Ball type mount built-in for easy installation
- Accidental Surge and Shock Protector Built-in.
- Reverse Polarity Power Protected
- Vandalproof, Weatherproof, Tamperproof
- Aluminum Housing & Polycarbonate Dome Cover Built-in
- Weatherproof (IP=66) for installing in the harshest conditions
- External Controls for both Distance and Focus.

HAWK-360VIRCD

SPECIFICATIONS

Pick up Device	1/3" Color Sony SuperHad CCD
TV System	NTSC
Picture Elements	510 (H) x 492 (V)
Horizontal Resolution	420 TVL
Sensitivity	0 Lux at f1.2 (infrared on)
Scanning System	525 TVL - 2:1 Interlace
Synchronization	Internal
Infrared Spectrum	850nm
S/N Ratio	More than 48db, (AGC off)
Auto Gain Control (AGC)	Auto
White Balance	Auto
Electronic Shutter	Auto
Back Light Compensation	Auto
Infrared LED	24 LED's
Infrared LED Range	60'
Video Output	1 Vp-p, 75 Ohm composite
Audio Output	N/A
Mirror Image	N/A
Gamma Ratio	0.45
Auto-iris Lens Control	N/A
Lens	f 4.0 - 9.0 mm Varifocal Lens
Exterior Focus Adjustment	Available
Lens Mount	M12XPO 5mm thread
Pan Adjusting	Manual
Tilt Adjusting	Manual
Power Supply	12V DC - 2.1mm DC Jack
Power Consumption	380 mA
Dimensions (ø X H)	4.7" x 4.3"
Net Weight	3.5 lbs
Weatherproof/Water Proof	Weatherproof
Operating Temperature	-4°F to +122°F